

Fork Oil
Applications
Castrol Fork Oil 20W is an advanced mineral based suspension fluid designed to provide superior damping performance in all on and off road suspensions.
Castrol Fork Oil is suitable for suspension damper units for on and off road motorcycles (including motocross) and road machines from Yamaha, Honda, Kawasaki and European makes.
Features / Benefits
Castrol Fork Oil provides the following benefits:
limproved damping performance over a wide range of temperatures Ifast air release for anti-fade performance Iwear protection of suspension components Iprotection against corrosion of all the internal parts
Specifications / Performance
Storage
All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions
Health, Safety and Environment
Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.  Castrol (UK) Ltd. or its subsidiaries will not accept liability if the product is used other than in the manner or with the precautions or for the purpose/s specified. Before the product is used other than as directed, advice should be obtained from the local Castrol office.
Typical Characteristics
Test Methods Units Value:

TEST	DATA
Density @ 20°C, Kg/m³	0.879
Viscosity at 100°C, mm²/s	11.2
Viscosity at 40°C, mm²/s	68
VI	150
Pour Point °C	-39

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Data sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

Castrol UK Ltd, Wakefield House, Pipers Way, SWINDON, Wiltshire. SN3 1RE www.castrol.com/uk

Telephone: 01793 512712

Automotive Technical Helpline: 01793 452222

Orders/Enquiries: 0845 6008125 (Workshop Customer Order Line) 0845 6008131 (Retail Customer Order Line)

Castrol Ireland, Suit 12, Plaza 212, Blanchardstown Business Park Phase 2, Blanchardstown, DUBLIN 15, Ireland www.castrol.com/ie

Automotive Technical Helpline: 1800 509 353 Orders/Enquiries: 01 866 5100

Date of issue: 14-Jun-2004